

Amendments to the Claims

1. (Original) A method of enabling a proxy client in a secured network to access a target service on behalf of a user, comprising the steps of:
  - registering proxy authorization information regarding the user with a trusted security server, the proxy authorization information identifying the proxy client and an extent of proxy authorization;
  - submitting, by the proxy client, a proxy request to the trusted security server requesting access to the target service on behalf of the user;
  - comparing, by the trusted security server, the proxy request with the proxy authorization information of the user to determine whether to grant the proxy request;
  - issuing, by the trusted security server, a data structure containing authentication data recognizable by the target service for authenticating the proxy client for accessing the target service on behalf of the user.
2. (Original) A method as in claim 1, wherein the data structure is a ticket containing a session key for use in a session formed between the proxy client and the target service.
3. (Original) A method as in claim 1, wherein the ticket is encrypted with a secret key shared by the target service and the trusted security server.
4. (Original) A method as in claim 1, wherein the step of comparing determines whether a proxy duration specified by the proxy authorization information has expired.
5. (Original) A method as in claim 1, wherein the step of submitting the request includes transmitting a ticket for authenticating the proxy client to the trusted security server.

In re Application of: Swift et al.  
Application No.: 09/490,199

6. (Original) A computer-readable medium having computer-executable instructions for performing steps:
- storing proxy authorization information from a user for authorizing a proxy client to act as a proxy of the user;
  - receiving a proxy request from the proxy client to access a target service on behalf of the user;
  - determining, based on the proxy authorization information of the user, whether to grant the proxy request;
  - constructing a data structure containing authentication data recognizable by the target service for authenticating the proxy client for accessing the target service on behalf of the user.
7. (Original) A computer-readable medium as in claim 6, having further computer-executable instructions for performing the step of authenticating the user based on a password of the user before storing the proxy authorization information.
8. (Original) A computer-readable medium as in claim 6, wherein the step of receiving the proxy request includes authenticating the proxy client based on a ticket issued to the proxy client for communicating with the trusted security server.
9. (Original) A computer-readable medium as in claim 6, having further computer-executable instructions for performing the step of sending the data structure to the proxy client for presenting to the target service for authentication of the proxy client.
10. (Original) A computer-readable medium as in claim 6, wherein the data structure is encrypted with a key shared by the target service and the trusted security server.

In re Application of: Swift et al.  
Application No.: 09/490,199

11. (Original) A computer-readable medium having computer-executable instructions for a client in a secured network system to perform the steps of:

submitting a proxy request to a trusted security server, the proxy request identifying a user and a target service that the client intends to access on behalf of the user;

receiving from the trusted security server a session key encrypted with a shared secret key shared by the client and the trusted security server and a ticket for accessing the target service;

decrypting the session key with the shared secret key;

constructing an authenticator encrypted with the session key;

presenting the authenticator and the ticket to the target service for authentication of the client for access of the target service on behalf of the user.

12. (Original) A computer-readable medium as in claim 11, wherein the step of submitting the proxy request includes sending a ticket issued to the client for authenticating the client to the trusted security server.

13-17. (Cancelled)

---